

0930006

File Number: EX15443

COMPANY

ELIMINATOR L L C

729 W LA CADENA DR
RIVERSIDE, CA 92501-1338 United States

MODEL INFO

0930006 High Flow Extinguisher
Potassium Bicarbonate, Cartridge-activated-type

GENERAL

Min Use Temp, °F (°C)

-40 (-40)

EXTINGUISHER CAPACITY AND MINIMUM TEMPERATURE

Nominal Agent Capacity, lb (kg)

9.9 (4.49)

EXTINGUISHER RATINGS

Class A Rating	Class B Rating	Class C Rating	Class K Rating	Marine Rating
--	20-B	Yes	No	Yes



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."